



ALTRA 187

THE MOST RESILIENT SOLUTION.

Since 1895, NIEDNER has been redefining the fire industry by creating lighter, more versatile lay flat hoses to overcome the challenges firefighters face. What makes firefighters around the globe trust NIEDNER's solutions is first and foremost the high quality and resiliency of the products. The hoses have been engineered to meet the most demanding applications, including heat and abrasion resistant fire hoses.

COMBAT LARGE SCALE FIRES

Fire departments and emergency response teams across North America rely on our field-proven firefighting hose technology ALTRA Fire to combat small to large scale fires. The unique attributes of our technology set the standard for the industry. ALTRA 187 is an extremely lightweight all synthetic forestry lay flat hose, which meets or exceeds USFS 5100-187 and ULC S518.1 specifications. This most widely used forestry hose is made of 100% filament polyester and is lined with TPU elastomer. ALTRA 187 is rated for 300 PSIG (2100 kPa) service test pressure. Being very lightweight and compact allows more of this hose to be packed and carried than other forestry hose products.

HIGHEST LEVEL OF QUALITY

NIEDNER maintains the highest levels of quality in the design, manufacturing, and testing of all our products. As a result, our solutions exceed the recognized international standards.

UNIQUE SERVICES

Our solutions have many advantages, including our unique services and engineering support which is second to none.



Highly safe hose



Corrosion and maintenance free



Short lead-times and quick to install



Reusable



Standard length: 50/100 feet



Increased resiliency



Commitment to the environment

Formally known as SPEC 187



FEATURES

- Abrasion and puncture resistance
- Transfer at higher pressures
- Kink resistant
- Ozone and age resistant
- Mildew and bacteria resistant

DESIGN

- Made of 100% filament polyester
- Lined with TPU elastomer

ADVANTAGES

- Lightweight and compact
- Easily packed and carried
- Certified to USFS* 5100-187 and ULC S518.1 specifications
- Temperature range: -60°F to 140°F (-51°C to 60°C).

CERTIFICATIONS FOR OUR PRODUCT LINE

NIEDNER's solutions are certified by accredited independent institutes



* US Forestry Service

TECHNICAL DATA

Diameter		Weights				Flat Width		Thickness		Coil Diam.				Coupling		Internal		Pressure	
Inches (mm)	Spec #	50 ft. w/alum cplgs		100 ft. w/alum cplgs		All lengths		Layflat		100 ft. w/Couplings		50 ft. w/Couplings		Bowl Size		Diameter		Service Test	
		Lbs.	Kgs.	Lbs.	Kgs.	in	cm	in	cm	in	cm	in	cm	in	mm	in	mm	PSI	kPA
1" (25mm)	5090	5	2.27	9	4.08	1.79	4.55	0.115	0.29	17	43.18	12.5	31.75	1-3/16	29.97	1"	25	300	2100
1 1/2" (38mm)	5095	7	3.18	14	6.35	2.56	6.50	0.120	0.31	18	45.72	14.25	36.20	1-11/16	42.67	1 1/2"	38	300	2100

AVAILABLE COLORS: None

CONTACT

Name:
Title:
Phone:
Email:

NIEDNER | ALTRA

675 rue Merrill, Coaticook, Québec, J1A 2S2

NIEDNER-ALTRA.COM